

CULTEC, Inc.
 878 Federal Road
 P.O. Box 280
 Brookfield, CT 06804, USA
Phone: 203-775-4416
Toll Free: 1-800-4-CULTEC (1-800-428-5832)
Fax: 203-775-1462
Email: custservice@cultec.com

Model # 100HD, Contactor 100HD

The Contactor[®] 100HD is a 12.5" (318 mm) high, low profile chamber and is typically used for installations with depth restrictions or when a larger infiltrative area is required. The Contactor 100HD has the side portal internal manifold feature. The HVLV™ SFCx2 Feed Connector is inserted into the side portal of the Contactor 100HD to create the internal manifold.

Available models:

Contactor 100RHD Heavy Duty Stand Alone/Starter Unit

Contactor 100EHD Heavy Duty Middle/End Unit

Check out our StormGenie Automated Drawing Program to design your Contactor 100HD Stormwater System.

Complete your preliminary calculations using our Stormwater Design Calculator.

[Click here to request our CULTEC Stormwater Design Guide.](#)



SPECIFICATIONS

Length	8.00 ft 2.44 m
Width	36 inches 914 mm
Height	12.50 inches 318 mm
Installed Length	7.5 ft 2.29 m
Length Adjustment per Run	0.50 ft 0.15 m
Chamber Storage	1.87 ft ³ /ft 14.93 ft ³ /unit 112 gal 0.17 m ³ /m 0.423 m ³ /unit 422.7 L

Min. Installed Storage - Intermediate	3.842 ft ³ /ft 28.81 ft ³ /unit 216 gal 0.36 m ³ /m 0.82 m ³ /unit 815.9 L
Min. Area Required per Unit	25 ft ² 2.32 m ²
Min. Center to Center Spacing (Design Unit Width)	3.33 ft 1.02 m
Max. Allowable Cover	4.27 m 14 ft
Max. Inlet Opening in Endwall	10 in 250 mm
Side Portal Dimensions (H x W)	7 x 7.5 in 178 x 191 mm
Max. Allowable Pipe Size in Side Portal	6 in 150 mm
Compatible Feed Connector	HVLV SFCx2 Feed Connector